

HANDHELD CB RADIOS



COMMON FEATURES

- Portable or mobile operation
- Up to 5 mile* communication range
- Maximum legal RF output power (4 Watts)
- HI/LO Power selector switch
- Last channel memory
- Jacks for battery charging and optional accessory use
- One year limited warranty

Packages include: Radio unit with belt clip, "Rubber Duck" antenna, 12V DC power cord with cigarette lighter plug, carrying strap, owner's manual and FCC Rules - Part 95, Subpart D

HCB-30C and HCB-40WX also includes: NOAA Weather Network frequency card

* Range will vary, depending on type of antenna used and geography of surroundings.

HCB-40WX PRODUCT FEATURES

- 40 CB Channels with 10 weather frequencies
- Receives current National Weather Service broadcasts on one or more of seven separate frequencies and periodic international marine weather information on three separate frequencies
- Direct access to Emergency CH 9
- Multifunctional LCD shows CB or weather channel selections, radio status icons and signal/power strength meter
- Soft-touch buttons for weather mode, up/down channel selection, display light and keypad lock

HCB-30C PRODUCT FEATURES

- 40 CB Channels with 3 weather frequencies
- Receives current National Weather Service broadcasts on one or more of three separate frequencies
- Side-mounted CB/Weather selector switch
- LED Channel display
- Transmit "TX" LED indicator
- Weather "WX" LED indicator
- Battery low LED indicator

HCB-10C PRODUCT FEATURES

- 40 CB Channels
- LED Channel display
- Transmit "TX" LED indicator
- Battery low LED indicator

ACCESSORIES/OPTIONS

- Telescopic antenna (WTA-1)
- Magnetic mount mobile CB/weather antenna (WTA-4W)
- Single AA Ni-Cad battery (2ABAT)
- AC/DC Wall charger (DV-7210)
- Voice-operated/push-to-talk mini-VOX headset (WTA-13G)
- Ear bud speaker with in-line P-T-T and microphone (QPA-1405)
- Lapel speaker/microphone (QPA-1425)

SPECIFICATIONS

GENERAL

CB Channels:	40
CB Frequency Range:	26.965 - 27.405 MHz
Weather Frequencies:	
HCB-40WX (10) 01-00	01 162.550 MHz
HCB-30C (3) 01-03	02 162.400 MHz
	03 162.475 MHz
	04 162.425 MHz
	05 162.450 MHz
	06 162.500 MHz
	07 162.525 MHz
	08 161.650 MHz
	09 161.775 MHz
	00 163.275 MHz

Frequency Control:	Phase Locked Loop Synthesizer
Power Source:	9 AA Alkaline or Ni-Cad batteries
Dimensions (H x W x D):	7-1/4" x 2-1/4" x 1-3/4" (184 x 57 x 44 mm)

Weight w/o batteries:	
HCB-40WX	9.6 oz. (272 g)
HCB-30C	9.4 oz. (266 g)
HCB-10C	9 oz. (255 g)

RECEIVER

Receiving System:	AM Dual conversion superheterodyne
DC Input Power:	5 Watts
Intermediate Frequency:	1st IF: 10.695 MHz 2nd IF: 455 MHz

TRANSMITTER

RF Output Power:	4W (Maximum FCC allowable)
------------------	----------------------------

Specifications are subject to change without notice.

About Maxon:

Maxon manufactures a full line of personal electronic products, including handheld and mobile CB radios, GMRS / DOT two-way radios, 49 MHz personal communicators, FRS radios, weather monitors and a variety of optional accessory items.

maxon[®]

A World of Communications

Maxon America, Inc. • Consumer Products Division
10828 NW Air World Drive • Kansas City, Missouri 64153
Phone: 1-800-821-7848, Ext. 399 • Fax: 816/891-8815
www.maxonusa.com